



HID FLOODLIGHT 250/400-WATT (E-HR4P25QZ, E-HR4P32QZ, E-HR4P40QZ, E-HR4H25QZ, E-HR4H40QZ)

Applications – Building facades and displays. Also effective as security lighting, for storage areas and commercial sites. Not for use as uplight.

Typical Mounting Height: 15 to 30 feet

Typical Spacing: (250W) 2 to 3 times the mounting height (400W) 2 to 4 times the mounting height



16-1/2"H x 16-1/2"W x 7"D
One mogul base lamp included

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Lamp Output	Lamp Color Rendition
E-HR4P25QZ	250-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V CWA Ballast HPF	E39	Mogul Base	29 Pounds	22000 lumens	65 CRI
E-HR4P32QZ	320-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V CWA Ballast HPF	E39	Mogul Base	29.5 Pounds	30000 lumens	65 CRI
E-HR4P40QZ	400-watt Pulse Start Metal Halide (PSMH)	120/208/240/277V CWA Ballast HPF	E39	Mogul Base	31.5 Pounds	40000 lumens	65 CRI
E-HR4H25QZ	250-watt High Pressure Sodium (HPS) Floodlight	120/208/240/277V CWA ballast HPF	E39	Clear, mogul base (~HP250)	31 Pounds	26000 lumens	22 CRI
E-HR4H40QZ	400-watt High Pressure Sodium (HPS) Floodlight	120/208/240/277V CWA ballast HPF	E39	Clear, mogul base (~HP400)	32.5 Pounds	48000 lumens	22 CRI

Features

- Sturdy die-cast aluminum housing and lens frame, with dark-bronze polyester powder-coat finish
- Tempered-glass lens, thermal-shock and impact resistant
- Fixture comes without mounting.
(Order E-ACS slip fitter or E-ACU U-bracket)
- UL Listed for wet locations
- 1-year warranty

Accessories



Photocell, field installed, use with E-ACS slip fitter only

CAT.#: E-ACP1 (120 volts)
CAT.#: E-ACP2 (208/240/277 volts)

Mounting options



Adjustable slip fitter.
Fits over 2-3/8" O.D. pipe
CAT.# E-ACS



Adjustable U-bracket, with 30" cord.
2-1/2"H x 5-1/2"W x 6"D
CAT.# E-ACU