



## FLUORESCENT WALL PACK 42-WATT (E-WP1F421Z)

**Applications** – Security, pathway and perimeter lighting; ideal for entry ways, walkways and parking facilities.

**Typical Mounting Height:** 8 to 18 feet

**Typical Spacing:** 2 to 3 times the mounting height



**9-1/2"H x 9-1/8"W x 9-1/2"D**  
One lamp included

Catalog #	Description	Ballast	Lamp Base	Lamp	Weight	Lamp Output	Lamp Color Rendition
<b>E-WP1F421Z</b>	42-watt Fluorescent Wall Pack	120-volt Electronic ballast	Heavy duty Four-pin GX24q-4	4 Pin, triple tube (~CF42T4/41)	3.6 Pounds	3190 lumens	82 CRI

### Features

- Sturdy die-cast aluminum housing and lens frame, with dark-bronze polyester powder-coat finish
- UV stabilized prismatic polycarbonate refractor
- One-piece anodized aluminum reflector
- 1/2-inch NPT tapped back and two sides for conduit entrances
- Optional photocell available
- Minimum starting temperature 32°F
- UL Listed for wet locations
- 1-year warranty

### Accessories



Photocell, field installed

**CAT.#: E-ACP1** (120 volts)

**CAT.#: E-ACP2** (208/240/277 volts)