


**WALL PACK
23/28 WATT LED
(E-WP2L SERIES)**

Applications – Security, pathway and perimeter lighting; ideal for entryways and other applications where control of spill light is important.

Typical Mounting Height: 8 to 15 feet

Typical Spacing: 1 to 2 times the mounting height



4-1/2"H x 8-3/4"W x 9-1/2"D

Catalog #	Description	Input Voltage	Delivered Lumen Output	CCT	CRI	Lifetime (L ₇₀ at 25°C)	Weight	Comparable To:
E-WP2L02CZ	23W LED Cool white	120V-277V	1500 Lumens	5600K	65	50,000 Hours	7 lbs	35W HID
E-WP2L03CZ	28W LED Cool white	120V-277V	1800 Lumens	5600K	65	50,000 Hours	7 lbs	50W HID
E-WP2L03NZ	28W LED Neutral white	120V-277V	1700 Lumens	4100K	80	50,000 Hours	7 lbs	50W HID

Features

- 50,000 hours of maintenance-free operation to L₇₀ at 25°C
- Die-cast aluminum housing and lens frame
- Dark bronze polyester powder-coat finish
- Fixed cutoff glare shield to reduce light pollution
- Tempered glass lens, thermal shock and impact resistant
- Mounts over horizontal, single-gang, recessed junction box or with conduit
- Die-cast back box for easy mounting
- 75°C minimum supply wire required
- Universal voltage (120V through 277V)
- High-powered LED array
- Heat dissipating fins
- Conduit entries on all sides of the fixture
- Knockout provided
- RoHS compliant
- UL Listed for wet locations
- 3-year warranty

Accessories



Photocell, field installed

CAT.#: E-ACP1 (120 volts)

CAT.#: E-ACP2 (208/240/277 volts)